

BLANK PAGE



Indian Standard "RL-1FFIRMED 1997 SPECIFICATION FOR "RL-1FFIRMED 1997 ANODIZED ALUMINIUM FOR AUTOMOBILE USE

(Second Reprint AUGUST 1985)

UDC 669.716.915:629.113



@ Copyright 1973

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

Indian Standard

SPECIFICATION FOR ANODIZED ALUMINIUM FOR AUTOMOBILE USE

Metallic Finishes Sectional Committee, SMDC 23

Chairman

Representing

DR S. KRISHNAMURTHY

Indian Telephone Industries Ltd, Bangalore

International Nickel (India) Pvt Ltd, Bombay

Members

Dr S. N. Anant Narayan

Canning Mitra Phoenix Ltd, Bombay

SHRI AHINDRA CHATTERIEE SHRI S. V. KULKARNI (Alternate)

Sen-Raleigh Ltd, Asansol

SHRI D. K. CHATTERJEE CHEMIST & METALLURGIST.

Ministry of Railways

INTEGRAL

COACH FACTORY, PERAMBUR

CHEMIST & METALLURGIST II.

RESEARCH, DESIGNS AND STANDARDS ORGANIZATION, LUCKNOW (Alternate)

SON LDR M. C. CHOUDHURY

Hindustan Aeronautics Ltd, Kanpur

SHRI B. V. K. RAO (Alternate)

Kohinoor Electro-Gilders, Bombay

SHRI KANTILAL T. DALAL SHRI JAYENDRA K. DALAL (Alternate)

SHRI P. N. GANDHI

The Indian Tube Company (1953) Ltd, Jamshedpur

SHRI D. D. BHUPTANI (Alternate)

GENERAL MANAGER, P & T WORK- Directorate General of Posts & Telegraphs, Calcutta

DEPUTY GENERAL MANAGER (Alternate)

Bharat Electronics Ltd, Bangalore SHRI M. N. KESARI

SHRI K. GURURAJA (Alternate)

Directorate General, Ordnance Factories (Ministry of Defence), Calcutta

SHRI V. KRISHNAN

SHRI K. D. BOSE (Alternate) SHRI U. G. K. MENON

Ministry of Defence (R & D)

SHRI S. L. N. ACHARYULU (Alternate)

Jeewanlal (1929) Ltd, Calcutta SHRI G. K. MIRCHANDANI

SHRI B. K. MURTHY Indian Aluminium Company Ltd, Calcutta

SHRI N. GOPALKRISHNAN (Alternate)

Arim Metals Industries Pvt Ltd, Calcutta SHRI J. C. NANGIA

SHRI S. K. NANGIA (Alternate)

SHRI S. PANCHPAKESAN

SHRI DILIP PAUL

T. I. Cycles of India, Madras Guest, Keen, Williams Ltd, Calcutta

DR K. S. RAJAGOPALAN

Central Electrochemical Research Institute (CSIR). Karaikudi

SHRI B. A. SHENOI (Alternate)

(Continued on page 2)

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI

IS: 6651 - 1972

(Continued from page 1)

Members

SHRI N. M. RAJU Hindustan Motors Ltd, Calcutta SHRI V. RAMASWAMY Ministry of Defence (DGI)

Shri M. Y. Borker (Alternate)
Shri R. K. Rokade
The Premier Automobiles Ltd, Bombay

SHRI P. K. DESHPANDE (Alternate)
SHRI N. C. ROY
Geep Flashlight Industries Ltd, Allahabad

Shri K. A. Siddiqui (Alternate)

SHRI K. K. SAMUEL Trivandrum Rubber Works Ltd, Trivandrum
SHRI SURESH R. SHAH Grauer and Weil (India) Ltd, Bombay
SHRI SUSHIL GOINKA (Alternate)

SHRI R. A. SHAH Ronuk Industries Ltd, Bombay Kumari Mridula A. Shah (Alternate)

SHRI D. S. TANDON National Metallurgical Laboratory (CSIR),

Jamshedpur

SHRI S. K. RAY (Alternate)
SHRI R. K. SRIVASTAVA,
Deputy Director (Struc & Met)

Director General, ISI (Ex-officio Member)

Secretary

Shri S. L. Bali Deputy Director (Met), ISI

Panel for Anodized Aluminium, SMDC 23: P16

Convener

SHRI G. K. MIRCHANDANI

Members
Shri V. K. Agrawal

CHEMIST & METALLURGIST,
INTEGRAL COACH FACTORY,
PERAMBUR

SHRI KANTILAL T. DALAL SHRI P. N. DESAI SHRI N. GOPALKRISHNAN

SHRI S. K. KHASNOBIS

Shri P. S. Mani

SHRI R. K. ROKADE DR R. C. SHARMA SHRI K. M. SRINIVASAN SHRI C. D. VARGHESE Jeewanlal (1929) Ltd, Calcutta

Hindustan Aluminium Corporation Ltd, Renukoot Ministry of Railways

Representing

Kohinoor Electro-Gilders, Bombay
Excell Process Ltd, Bombay
Indian Aluminium Company Ltd, Calcutta
Hindustan Motors Ltd, Hoogly
Director General, Ordnance Factories (Ministry of
Defence), Calcutta
The Premier Automobiles Ltd, Bombay
The Eveready Flashlight Co, Lucknow
Bharat Electronics Ltd, Bangalore
Hindustan Aeronautics Ltd, Bangalore

Indian Standard SPECIFICATION FOR ANODIZED ALUMINIUM FOR AUTOMOBILE USE

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 25 October 1972, after the draft finalized by the Metallic Finishes Sectional Committee had been approved by the Structural and Metals Division Council.
- 0.2 Various thicknesses of anodic coatings have been specified in IS: 1868-1968* for different applications. Three grades of anodic coatings, that is, AC 2.5, AC 5 and AC 10 have been selected for anodized aluminium for automobile use. For the sake of guidance, aluminium and its alloys used in the form of sheet and strip, extrusions and castings for different applications have been suggested in Appendix A. Designations for aluminium and its alloys given in Appendix A have been adopted from IS: 6051-1970†. However, the relevant Indian Standard designations have also been included in brackets for ready reference.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960‡. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies three grades of anodized aluminium for automobile use. This standard, however, does not cover requirements for reflectors.

2. SUPPLY OF MATERIAL

2.1 General requirements relating to supply of material shall conform to IS: 1387-1967§.

^{*}Specification for anodic coatings on aluminium (first revision).
†Code for designation of aluminium and its alloys.

[‡]Rules for rounding off numerical values (revised).

[§]General requirements for the supply of metallurgical materials (first revision).

3. FINISH AND APPEARANCE

- 3.1 The surface finish and appearance of the components and the method by which this is achieved shall be subject to agreement between the purchaser and the supplier. Inspection with regard to finish shall normally be carried out by direct visual comparison with a master sample.
- 3.2 Samples At the purchaser's request, the supplier shall submit samples at the time of the original quotation, such samples being fully representative of the material and components to be supplied.

4. GRADES

4.1 Anodized aluminium for automobile use shall be of the following three grades:

Grades	A pplication				
AC 2·5	For interior decorative applica- tions				
AC 5	For exterior decorative applica- tions and interior protective applications				
AC 10	For exterior applications where maximum protection is required				

5. REQUIREMENTS

5.1 Thickness — The minimum thickness of anodic coating in micrometres (μm) for the three grades shall be as given below:

Grades	Thickness (µm)				
AC 2.5	2.5				
AC 5	′ 5				
AC 10	10				

- 5.1.1 Thicknesses of coating shall be determined by the stripping or microsection methods specified in IS: 5523-1969* or with the help of instruments based on eddy current principle (see IS: 6012-1970†).
- 5.2 Corrosion Resistance The surface of the anodized articles of Grades AC 5 and AC 10, when subjected to copper-accelerated acetic acid salt spray (CASS) test as prescribed in IS:5528-1968‡ for 8 hours and

^{*}Methods of testing anodic coatings on aluminium.

[†]Method for measurement of coating thickness by eddy current.

[†]Method of testing corrosion resistance of electroplated and anodized aluminium coatings by copper-accelerated acetic acid salt spray (CASS) test.

12 hours respectively, shall be free from significant signs of corrosion. Articles of Grade AC 2.5, however, when subjected to acetic acid salt test as prescribed in 'Indian Standard method of testing corrosion resistance of electroplated and anodized aluminium coatings by acetic acid salt spray test' for 24 hours shall not show any significant sign of corrosion.


- 5.3 Abrasion Resistance The abrasion resistance of the anodic coating shall be tested by the abrasion test given in IS: 5523-1969*. The test requirements, however, shall be mutually agreed upon between the supplier and the purchaser.
- 5.4 Sealing The surface of the anodized article shall show no milkiness when tested in accordance with the sulphur dioxide test described in IS:5523-1969*.
- 5.5 Brightness The test requirements, wherever required, shall be agreed to between the supplier and the purchaser.

6. MARKING

- 6.1 The anodized articles shall be marked with the grade of the coating and the name or trade-mark of the manufacturer. The supplier shall furnish a certificate that the material supplied complies with the requirements of this specification.
- 6.1.1 The articles may also be marked with the ISI Certification Mark. The supplier's certification (see 6.1) shall be complied, if the material is certified under the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

^{*}Methods of testing anodic coatings on aluminium.



APPENDIX A

(Clause 0.2)

CHEMICAL COMPOSITION OF CAST AND WROUGHT ALUMINIUM AND ALUMINIUM ALLOYS FOR ANODIZING

(Composition limits are in percent maximum unless shown as a range)

			(Comp	JOSILION			Perce	HE IIIA	WITH COLD	tallite 31	3 3110		5-	•	
Designation	Aluminium	Copper	MAGNE- SIUM	SILI- CON	Iron	Manga- nese	Nickel	Zinc	LEAD	Tin	TITA- NIUM PLUS NIO- BIUM	TITA- NIUM AND/OR OTHER GRAIN REFIN-	CHRO- MIUM	Remarks	Applications
												ING ELE- MENTS			
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)
	4				Cz		inium A	lloys fo		Anodizi	ng				
5230 (A-5)	Remainder	0.1	3.0 to	0.3	0.6	0.3 to	0.1	0.1	0.05	0.05	0.2	_		– }	· A
5500 (A-10)	Remainder	0.1	6·0 9·5 to 11·0	0.25	0.35	0·7 0·10	0-10	0.10	0.05	0.05	0-2	_	_	- }	Automobile fittings and hardware
					Cas	t Alumi	nium All	oys for	Protectiv	ve Anod	izing			_	
4250 (A-8)	Remainder	0.1	0·3 to 0·8	3·5 to 6·0	0.6	0.5	0.1	0.1	0.1	0.05	0.2			-	Cylinder block, crank case, cylinder head,
4225 (A-16)	Remainder	1.0 to 1.5	0·4 to 0·6	4·5 to 5·5	0.6	0.5	0.25	0.1	0.05	0.05				-	pulley, wheel rim Cylinder barrel housing
4223 (A-22)	Remainder	2·8 to 3·8	0.05	4·0 to 6·0	0.7	0.3 to	0.15	0-15	0.05	0.02	0.2		_		Transmission cases, fly wheel housings
				,	Wrougi	it Alum	inium ar	d its Al	loys for	Bright A	Anodizin	g			
19700	99·7 minimum	0.03		0.2	0.25	0.03	_	0.06	. 	_	_		_	Cu+Si+Fe+Mn+Zn=0.3	Name-plates, mono- grams and other small intricate parts
19500 (IB)	99.5 minimum	0.05		0.3	0-4	0.05	_	0-1	_					Cu+Si+Fc+Mn+Zn=0.5	Patterned sheet for trim applications
19000 (1C)	99·0 minimum	0.1	_	0.5	0.7	0.1		0.1	_	_		_		Cu+Si+Fe+Mn+Zn=1.0	General application, door sill, etc
51000-A	Remainder	0.2	0·5 to 1·1	0.6	0.7	0.5	-	0.25		_	-	_	0-1	MII+ZII=10	,
														Į	Grills, mouldings, win- dow trim, kick pad,
52000 (N4)	Remainder	0.1	1.7 to 2.8	0.6	0.7	0.5	<u>«</u>	0.2			_	0.2	0.25	Cr+Mn=0.5	kick protector, etc
53000 (N5)	Remainder	0.1	2.8 to	0.6	0.7	0.5	_	0.2				0.2	0.25	Cr+Mn=0.5	Hub, wheel hub, bum-
63400 (H9)	Remainder	0.1	4·0 0·4 to 0·9	0·3 to 0·7	0.6	0.3		0.2		_	_	0.2	0-1		per, etc Extruded mouldings & trims; interior trim, fascia panels, grills, tread strip, etc
	Wrought Aluminium Alloys for Protective Anodizing														
65400 (H19)	Remainder	0.1	0.4 to 1.5	0.6 to 1.3	0.6	0.2		0-1	-			0.5	0.1		Platform and struc- turals of commercial vehicle

INDIAN STANDARDS INSTITUTION

The state of the case of	AND RESIDENCE
Headquart	BEE BUILDING

fire divisions.	
Manak Bhavan, 9 Bahadur Shah Zafar Marg	
NEW DELHI 110002	
Telephones: 331 0131 Telegra	ms : Manaksanstha
331 1375 (Com	mon to all Offices)
Regional Offices:	Telephone
*Western : Manakalaya, E9 MIDC, Marol Andheri (East) BOMBAY 400093	6 32 92 95
† Eastern : 1/14 C. I. T. Scheme VII M V.I.P. Road, Maniktola CALCUTTA 700054	36 24 99
Northern : SCO 445-446, Sector 35-C CHANDIGARH 160036	{ 2 18 43 3 16 41
Southern : C. I. T. Campus MADRAS 600113	{ 41 24 42 41 25 19 41 29 16
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpur AHMADABAD 380001	{ 2 63 48 2 63 49
F' Block, Unity Bldg, Narasimharaja Square BANGALORE 560002	22 48 05
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar BHOPAL 462003	6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002 53/5 Ward No. 29, R. G. Barua Road, 5th Byelane GUWAHATI 781003	5 36 27
5-8-56C L. N. Gupta Marg. HYDERABAD 500001	22 10 83
R14 Yudhister Marg. C Scheme, JAIPUR 302005	{ 6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	{ 21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
Hantex Bldg (2nd Floor), Rly Station Road, TRIVANDRUM 6950	001 52 27
Inspection Office (With Sale Point):	
Institution of Engineers (India) Building, 1332 Shivaji Nagar PUNE 411005	5 24 35
*Sales Office in Bombay is at Novelty Chambers, Grant Road BOMBAY 400007	89 65 28
†Sales Office in Calcutta is at 5 Chowringhee Approach P.O. Princep Street, CALCUTTA 700072	27 68 00